



DGS-3627

```
config vlan default delete 21-24
create vlan 2 tag 2
config vlan 2 add tagged 21
create vlan 3 tag 3
config vlan 3 add tagged 22
create vlan 4 tag 4
config vlan 4 add untagged 23
```

```
config ipif System ipaddress 1.1.1.1/24
create ipif 4 10.244.0.254/24 4
create ipif 2 10.245.10.254/24 2
create ipif 3 10.246.10.254/24 3
```

```
config rip all tx_mode v2_only rx_mode v2_only state enable
enable rip
```

=====

DGS-3650-1

```
config vlan default delete 1-48
create vlan 2 tag 2
config vlan 2 add tagged 48
create vlan 5 tag 5
config vlan 5 add tagged 1-2
```

```
config ipif System ipaddress 1.1.1.2/24
create ipif 5 10.244.5.253/24 5
create ipif 2 10.245.10.253/24 2
```

```
config rip all tx_mode v2_only rx_mode v2_only state enable
enable rip
```

```
create vrrp vrid 5 ipif 5 ipaddress 10.244.5.1 state enable
enable vrrp
enable vrrp ping
```

DGS-3650-2

```
config vlan default delete 1-48
create vlan 3 tag 3
config vlan 3 add tagged 48
create vlan 5 tag 5
config vlan 5 add tagged 1-2
```

```
config ipif System ipaddress 1.1.1.4/24
create ipif 5 10.244.5.254/24 5
create ipif 3 10.246.10.253/24 3
```

```
config rip all tx_mode v2_only rx_mode v2_only state enable
enable rip
```

```
create vrrp vrid 5 ipif 5 ipaddress 10.244.5.1 state enable
enable vrrp
enable vrrp ping
```

=====

DGS3450

```
config ipif System ipaddress 10.244.5.10/24
config vlan default delete 1-12
create vlan 5 tag 5
config vlan 5 add tagged 1-2
config vlan 5 add untagged 3-12
```