

How to configure the Default Gateway via SNMP on DGS-3200

Example

Configure default gateway to 10.90.90.99

```
#snmpset -v2c -c private 10.90.90.90 1.3.6.1.2.1.16.19.12.0 a 10.90.90.99
```



```
Administrator: Command Prompt
C:\Users\Anngu>snmpset -v2c -c private 10.90.90.90 1.3.6.1.2.1.16.19.12.0 a 10.90.90.99
SNMPv2-SMI::mib-2.16.19.12.0 = IPAddress: 10.90.90.99
C:\Users\Anngu>
```

```
DGS-3200-10:4#show iproute static
Command: show iproute static

Routing Table
IP Address/Netmask  Gateway  Hops  Protocol  weight  Status
-----
0.0.0.0/0          10.90.90.99  1     Default  None    Inactive
Total Entries : 1

DGS-3200-10:4#sh sw
Command: show switch

Device Type       : DGS-3200-10 Gigabit Ethernet Switch
MAC Address       : 00-22-B0-EC-55-5D
IP Address        : 10.90.90.90 (Manual)
VLAN Name        : default
Subnet Mask       : 255.0.0.0
Default Gateway   : 10.90.90.99
Boot PROM Version : Build 1.00.B006
Firmware Version  : Build 2.21.B006
```