

Save via SNMP on DES-3528

F/W: 2.21

MIB: AGENT-GENERAL-MIB.mib

OID: 1.3.6.1.4.1.171.12.1.2.6

agentBs	Object name	agentSaveCfg
agentBs	Object ID	1.3.6.1.4.1.171.12.1.2.6
agentBs	Module	AGENT-GENERAL-MIB
agentBs	Base syntax	Integer
agentBs	Composed syntax	INTEGER
agentBs	Access	Read-Write
agentBs	Status	Current
agentBs	Value list	<ul style="list-style-type: none">1 : other(1)2 : cfg-idl(2)3 : cfg-id2(3)4 : log(4)5 : all(5)
agentFileTransfer	Parent node	agentBasicConfig
agentSystemRe	First child	None
agentRs232Port	Description	This object indicates the type of save command to be executed, when saving to the NV-RAM. other (1) - none of the following. cfg-idl (2) - save configuration ID1. cfg-id2 (3) - save configuration ID2. log (4) - save log. all (5) - save both (active configuration and log).

Example:

The following command will save configuration to config_id 1

snmpset -v2c -c private 10.90.90.90 1.3.6.1.4.1.171.12.1.2.6.0 i2

indicates the type of save command to be executed, when saving to the NV-RAM.
other (1) - none of the following.
cfg-idl (2) - save configuration ID1.
cfg-id2 (3) - save configuration ID2.
log (4) - save log.
all (5) - save both (active configuration and log).